

STA-PUT “CLEAR” SEALER – PRIMER

STA-PUT CLEAR is an ACRYLIC SEALER that bonds to a variety of clean, dry surfaced to provide protection from the elements of weathering. It is recommended as a sealer over rock roofs, clay tile and clean wood shakes. It also effectively seals block walls.

APPLICATION:

Apply only when coating will not be subjected to rain before Sealer has dried. (Approximately 4 hours). Sealer should not be applied to dirty surfaces. Clear sealer should not be applied when roof temperature is less than 50 degrees F.

STA- PUT CLEAR is a “concentrate and should be cut 20 to 50% with water before using!!

CLEAN – UP:

Hands, tools and equipment may be easily cleaned in water if cleaned immediately after use. Use ISOPROPYL ALCOHOL after sealer is dry.

APPLY:

SPRAY, BRUSH OR ROLL

NOTE: PRODUCT IS MILKY WHITE IN LIQUID STATE, BUT WILL DRY TOTALLY CLEAR

SPECIFICATIONS:

SERVICE TEMPERATURE: 0 degrees F – 200 degrees F

SOLID CONTENT: 55%

FIRE RATING: CLASS A

WEIGHT: 10 lbs per gallon

DRYING TIME: - 2 to 4 hours.

PROTECT FROM FREEZING

DO NOT COMMENCE APPLICATION WHEN RAIN IS A POSSIBILITY



(480) 967-9407

3003 N. 73RD ST. SUITE 1 • SCOTTSDALE, ARIZONA 85251

HIGH PERFORMANCE ROOF COATINGS • PRIMERS • MEMBRANES
PATCHING COMPOUNDS • CAULKS • SEALANTS • DECK COATINGS