

# WHITE ACRYLIC (TROWEL GRADE) ROOF CEMENT

WHITE ACRYLIC CEMENT is a premium quality ELASTOMERIC patching compound, which combines ACRYLIC POLYMERS with a HI- SOLID content.

## PRODUCT USES:

WHITE ACRYLIC CEMENT can be used as a patching compound for filling voids and gaps in parapet walls. WHITE ACRYLIC CEMENT can also be used for filling large voids and sealing around penetrations or for sealing drains and scuppers. IT IS THE REPAIR PRODUCT FOR URETHANE FOAM ROOFS.

## PREPARATION:

Thoroughly clean off all dirt and debris.

## APPLICATION:

APPLY ONLY WHEN NOT SUBJECT TO RAIN.

Apply ¼ inch thickness or less. It needs 24 hours of SUNSHINE in summer to dry. Do not apply when roof temperature is less than 50 degrees F or when wet. Cure time depends on thickness!! ---- Several days in winter!!



(480) 967-9407

3003 N. 73RD ST. SUITE 1 • SCOTTSDALE, ARIZONA 85251

HIGH PERFORMANCE ROOF COATINGS • PRIMERS • MEMBRANES  
PATCHING COMPOUNDS • CAULKS • SEALANTS • DECK COATINGS